



WARNING: Validate the kit contents with the component list included on page 2 of this sheet before proceeding. This harness is intended to be used in a modified vehicle. Please read this sheet thoroughly and be sure that you understand everything explained on it prior to opening any of the enclosed packages, or before attempting to install any of the components. Once this kit has been opened or a component installed, the kit is not returnable. The new fusebox assembly is intended to be installed in the same approximate location as was the original, and the harness routed in the same fashion as was the original. The exact finished location of the new fusebox is not extremely critical as the new harness is long enough that it will install fine as long as the new fusebox is mounted in the general area of your stock original Corvette fusebox.

1. Grounding is extremely important with any Corvette due to the body being all fiberglass. Your new wire kit has been engineered to utilize all the stock ground wire locations used on an original car. As long as you have good clean grounding points, you should be OK. However, if your build is a bit more involved, you may want to consider the use of a complete vehicle assembly grounding system.
2. This kit only supports the use of a higher current self-exciting 1 wire, GM "SI" series, or other style internally regulated alternator. An adapter (that is not included with this kit) may be necessary for certain applications. The use of a stock, low amperage generator is seriously discouraged as it cannot handle the higher current requirements of updated ignition systems, electric fans, aftermarket A/C systems, stereo systems, air ride suspensions, and other power hungry accessories that will ultimately create performance issues with the system.
3. This kit WILL NOT support the use of a factory ammeter. This kit is engineered to supply the optimum charge to the battery. To achieve this performance, we route our 8ga. charge wire directly from the alternator output terminal to the starter solenoid. Due to the path of the charge being altered from the stock configuration, the gauge can no longer see a charge vs. a discharge, so it will not work properly. When ammeters were originally used, most generator current outputs were rated at a maximum of about 25-40 amps. Modified vehicles being built today typically utilize a 100 amp or higher output alternator. With these higher current units, ammeters, generally speaking, become a safety hazard. Ammeters are usually wired in parallel to the charging circuit, are typically unfused, and can short very easily causing a fire. A voltmeter is recommended as a good alternative.
4. This kit IS NOT set up with a resistance wire or a ballast resistor for a standard, points type ignition system. It is wired with a full 12 volt primary ignition feed that is hot in both the start and run positions. It will support HEI, MSD, other electronic ignition systems, as well as computerized Fuel Injection systems. If you wish to run a points type system, there are illustrations on the engine connection pages to do so. Extra parts that are not included in this kit will be required to complete that operation.

RESTO MOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

VCU5362

92973606 instruction sheet Rev 0.0 6/4/2021

VCU5362 - RestoMod Series Kit

1953-1962 Chevrolet Corvette

This kit contains the following components:

<u>Bag</u>	<u>Part Number</u>	<u>Description</u>	<u>Quantity</u>
	510621	Ignition Switch	1
	510284	Headlight Switch	1
	500919	Practice Terminal Crimping Set	1
	510145	Fuse, Relay, and Flasher kit	1
	510285	Floor Dimmer Switch	1
G	510894	Dash Harness kit	1
H	510278	Dash Cluster wiring kit	1
L	510915	Front Light and Main Power kit	1
M	510279	Rear Body Wiring kit	1
P	510280	Courtesy Light kit	1
N	510281	Headlight Connection kit	1
Z	510813	Alternator and Main Power Connection kit	1
	92969889	Firewall Mounting Template	1
	92973594	Instruction Sheet for 53-62 Corvette	1
	92973606	Warning Sheet	1

Validate the kit contents with this component list. If there are any discrepancies with incorrect or missing parts, stop your installation and notify the supplier you purchased the kit from before proceeding.

RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

VCU5362

RestoMod Series

1953 - 1962 Chevy Corvette

START HERE !

PLEASE READ THIS BEFORE STARTING INSTALLATION !

This wiring kit is designed for ease of installation. Please read the guidelines below, BEFORE STARTING your installation to guarantee a successful job. Use an appropriate crimping tool which folds the wings of the open barrel terminals down into the wire as shown below. ALL TERMINALS THAT YOU INSTALL SHOULD BE PROPERLY SOLDERED. Our factory crimped terminations are installed by GM approved five ton presses, and soldering these terminations is not necessary.



AS THIS HARNESS IS DESIGNED FOR USE IN A MODIFIED CAR REQUIRING A HIGHER RATE OF CHARGE, IT DOES NOT SUPPORT THE USE OF A STOCK (ORIGINAL) ALTERNATOR OR GENERATOR. IT IS DESIGNED FOR USE WITH AN INTERNALLY REGULATED GM "SI" STYLE OR SINGLE WIRE STYLE ALTERNATOR. ADAPTERS (WHICH ARE NOT INCLUDED WITH THIS KIT) ARE AVAILABLE FROM SEVERAL SOURCES WILL BE NECESSARY TO USE ANY ALTERNATOR OTHER THAN AN "SI" or 1 WIRE UNIT.

STEP 1: DISCONNECT YOUR BATTERY:

Disconnect the battery before installing the wiring kit to prevent any accidental shorting caused by loose bare wire ends.

STEP 2: START INSTALLING KIT:

This kit is broken down into individual steps that are identified by a letter printed on the instruction sheets visible through each bag. These letters are the order of operation for installing your kit. Start with bag letter G, then H, etc. The order of installation is shown below. Use this main instruction sheet, 92973594, to complete the installation process.

G - 510894 Dash Harness Kit
H - 510278 Gauge Cluster Kit
L - 510915 Front Light and Main Power Kit
M - 510279 Rear Body Kit
N - 510281 Headlight Bucket Kit
P - 510280 Courtesy Lamp Kit
Z - 510813 Alternator and Main Connection Kit

STEP 3: RECONNECT YOUR BATTERY:

When you have completed the installation and are ready to reconnect the battery, make sure that the following electrical system grounds are in place:

- A. Battery is grounded to the ENGINE BLOCK.
- B. Battery is grounded to the frame.
- C. Engine block is grounded to the frame.
- D. Body is grounded to the frame.

STEP 4: CHECK ALL ELECTRICAL FUNCTIONS:

Any non-functioning items should be checked for proper installation. Any problems with your wiring and electrical circuit functions should be addressed to Lectric Limited, Inc.. as soon as possible to avoid any warranty problems.

If you have any questions concerning this or any of our products, please feel free to call us at 1-708-563-0400.

RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

We carry many accessories for your 1953-1962 Corvette

p/n VCU5357EB
1953-57 parking brake
warning signal kit



p/n VCU5862EB
1958-62 parking brake
warning signal kit



p/n VCU6162TL
1961-62 optional 3rd
stop/tail lamp kit



p/n VCU6162BU
1961-62 optional
back up lamp kit



RestoMod Series


1953 - 62
Chevy Corvette

VCU5362


92973594 Rev. 0.0 5/31/2022

16	Fuel Pump 20A - IGN	8	Pwr Window 30A - IGN
15	Elec. Choke 15A - IGN	7	Hazard 15A - BAT
14	Gauges, B/U 10A - IGN	6	Stop/Courtesy 15A - BAT
13	Turn 15A - IGN	5	Power Locks 15A - BAT
12	Engine Fan 30A - ACC	4	Park Lights 15A - BAT
11	Radio 10A - ACC	3	Power Seat 30A - BAT
10	HeavAC 30A - ACC	2	Clock/Radio 15A - BAT
9	Wiper 20A - ACC	1	Batt - Spare 30A - BAT

Fuse label on inside of Fuse Box Cover



Fuse Installation Orientation



PART #

VCU5362


DESCRIPTION:

**1953-62 Chevy Corvette
RestoMod Series**


92973594 Rev. 0.0 5/31/2022

Bag

G



NOTE: wires 400 & 401 must be twisted together



Engine Harness Wiring




This engine harness extension will be used to complete the wiring out to the engine senders, coil (tach), electric speedometer (if so equipped), electric choke (if so equipped), and the internal alternator regulator plug. In a stock application, the only engine wire necessary would be the dark green temperature gauge wire. If you are using updated electric gauges (as opposed to the stock mechanical gauges), you will need to use some of these other wires. You will need to determine which of the wires you will need for your application and plug them into the engine harness extension plug above maintaining color continuity with the engine connector on the dash harness located at branch 4 on page 5. Once you have loaded the above plug with the necessary wires for your application, take the completed extension and plug it onto the engine connector, then route these wires along with the 2B, 3A, and 6 wires (located at branch 4 on page 5) out through your firewall to the engine bay. See page 10, Figure D for typical connections. See loose piece kit 510277 for any needed terminals and connectors.

Wire #	Wire color	Printing
31B	Dk. Blue	Oil Pressure
35B	Dk. Green	Temp Sender
39F	Tan	Electric Choke
121A	White	Coil Tach
25	Brown	Alt. Ign.
400A	Yellow	VSS Ground
401A	Purple	VSS Signal
402A	Purple/White	VSS Power

Procedure
Oil pressure wire from the engine connector to the oil pressure sender.
Temperature sender wire from the engine connector to the temperature sender.
12v ignition feed wire from the engine connector to the electric choke.
Tach sender signal wire from the engine connector to the coil or tach feed from your ignition system.
This is the low voltage feed wire from the engine connector to a GM Style "SI" internally regulated alternator.
VSS ground from the engine connector to the vehicle speed sensor. (must twist this with 401A)
VSS signal from the engine connector to the vehicle speed sensor. (must twist this with 400A)
VSS 12v fused power from the engine connector to the vehicle speed sensor.

Main Power and Alternator Connections

You can find all the parts and detailed installation instructions for the main power connections in the 510813 kit.



RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.
www.lectriclimited.com 708-563-0400

PART #

VCU5362

DESCRIPTION:

1953-62 Chevy Corvette RestoMod Series

92973594 Rev. 0.0 5/31/2022

Bag

G

Main Fuse Panel Installation Instructions

The Main Fuse Panel harness is designed to be mounted under the dash on the firewall in the same general area as did the stock harness. See photos of the installed fuse panel on the "fuse panel mounting template and instruction sheet", P/N 92969868. The enclosed representation of the main dash harness shows each circuit branch and identifies each connection by its color and function. Follow this drawing and detail drawings on pages 8, 9, and 10 for the individual circuit connections.

Circuit Branch 1 - Front Lighting connections

Wire #	Wire color	Printing
29	Dark Green	Horn
14A	Light Blue	Left Front Turn
15A	Dark Blue	Right Front Turn
300	Orange	Electric Fan
9A	Brown	Park Lights
11A	Light Green	Headlight-Hi Beam
12	Tan	Headlight-Low Beam

150H Black Ground

Ground Leads
150A,H Black Ground
152 Black/White Ground

Circuit Branch 1 - Underdash Connections

Wire #	Wire color	Printing
Dimmer Switch		
10	Yellow	Dimmer Switch Feed
11A, B	Light Green	Headlight Hi Beam
12	Tan	Headlight Low Beam
Accessory Wire Connector		

103	Tan	Fuel Pump
104	Orange	Power Seats
105	Red	Power Locks
100	Red	CB Radio
106	Pink	Power Window
107	Orange	Spare Battery

Circuit Branch 2- Underdash Connections

Wire #	Wire Color	Printing
Horn Relay		
2C	Red	12v Bat
28	Black	Relay Ground
29	Green	Horn

Flashers		
16, 16A	Purple	Turn Switch Feed
27, 27A	Brown	Hazard Switch Feed

Rear Body Connection

9B	Brown	Rear Running Lights
17B	Lt. Blue	Third Brake Light
18	Yellow	Left Rear Turn
19	Dk. Green	Right Rear Turn
24	Lt. Green	Back Up Lt Sw
30	Tan	Gas Gauge
40A	Orange	12v Battery Fused
150D, E	Black	Ground
152	Black/White	Ground

1953-57 LH Courtesy Connection		
40B, C	Orange	12v Battery Fused
156A, C	White	Ctsy Ground

LH Door Jamb Switch		
150C	Black	Ground
156C	White	Ctsy Ground

Ground		
150A,B	Black	Ground

Plug the front light connections from the 510915 Front Light and Main Power Kit onto the dash connections, then route the wires out through the firewall. See page 9, "Figure A" for typical connections. See loose piece kit 510894 for any needed terminals and connectors.

Procedure

Connect to the horn power terminal. NOTE: You also will need to run the black 150 wire to your horn's ground terminal in order for the horn to operate.

Connect to the blue wire that is in left front directional lamp lead (not included with this kit).

Connect to the blue wire that is in right front directional lamp lead (not included with this kit).

This is the 12 volt ignition feed to be connected to the trigger wire on your electric fan relay.

Connect to both the front park / running light lamp lead purple wires (not included with this kit). An in-line splice of this wire or a double up of this wire at the left front parking lamp will be necessary to accommodate the wiring of both of the front parking lights.

These wires will mate with the H/L connection kit harnesses, P/N 510281, to complete the front headlight connections. Use the supplied loose piece terminals and connectors in kit 510894 to make these connections to the 510281 H/L connection kit. Select the light green Headlight Hi Beam wire (11A) and tan Headlight Low Beam wire (12). Route these wires to the grill shell area near the LH headlight. Cut the wires to length, double the wires with the cutoff portions, crimp on terminals V and plug into connector N as shown on page 9, Figure A. Route the remaining portion of the wire to the opposite side of the grill shell near the RH headlight, cut to length, crimp on terminals W and plug into connector N as shown on page 9, Figure A. Do not plug these connections onto your 510281 H/L connection kit yet as the ground circuits must first be completed.

Take this wire to the left H/L area, cut to length, double with the cutoff portion and route to the LH P/L, cut to length, double with the cutoff portion and route to the LH horn, cut to length, double with the cutoff portion and route to the RH horn, cut to length, double with the cutoff portion and route to the RH P/L, double with the cutoff portion and route to the RH H/L. Use the terminals and connectors as shown on page 9 to complete the grounding circuit. Main chassis and fuel sender grounds. NOTE: These MUST be firmly attached to your block via the bellhousing bolts. Main chassis ground to bellhousing flange bolt for instrument cluster, lighting, and horn ground connections. Dedicated fuel tank sender ground to bellhousing flange bolt.

Take this wire to the left H/L area, cut to length, double with the cutoff portion and route to the LH P/L, cut to length, double with the cutoff portion and route to the LH horn, cut to length, double with the cutoff portion and route to the RH horn, cut to length, double with the cutoff portion and route to the RH P/L, double with the cutoff portion and route to the RH H/L. Use the terminals and connectors as shown on page 9 to complete the grounding circuit.

Main chassis and fuel sender grounds. NOTE: These MUST be firmly attached to your block via the bellhousing bolts.

Main chassis ground to bellhousing flange bolt for instrument cluster, lighting, and horn ground connections.

Dedicated fuel tank sender ground to bellhousing flange bolt.

Procedure

12v Feed from H/L switch

Switched 12v from dimmer to high beam lamps

Switched 12v from dimmer to low beam lamps

Use the provided connector L and terminals M as power leads for the following:

Fuse	Rating	
FUEL	20 amp	Fused 12 volt IGNITION feed for fuel pump (or another fused ignition circuit)
PWRSEATS	30 amp	Fused 12 volt BATTERY feed for power seats (or another fused battery circuit)
PWR LOCKS	15 amp	Fused 12 volt BATTERY feed for power door locks (or another fused battery circuit)
CB	15 amp	Fused 12 volt BATTERY feed for a CB radio (or another fused battery circuit)
PWRWDO	30 amp	Fused 12 volt ACCESSORY feed for power windows (or another fused accessory circuit)
BAT SPARE	30 amp	Fused 12 volt BATTERY feed (for any application)

Procedure

Plug the horn relay (found in the 510145 fuse kit) into this connector.

12 volt battery feed.

Relay ground circuit (to steering column).

Triggered 12 volts to horn.

Plug one each of the flasher cans (found in the 510145 fuse kit) into these connections.

Turn signal flasher leads.

Hazard flasher leads.

The main connector from the Rear Body Kit, 510279 will plug in here to complete the rear body connection.

12v feed for tail and tag lamps.

12v feed for optional 3rd brake lamp.

12v feed to the LH rear stop and turn lamp.

12v feed to the RH rear stop and turn lamp.

12v feed to the back up lamps (optional kit, P/N 510332, available).

Fuel sender signal wire between the rear body and cluster connections.

12v battery feed for LED lamps or trunk lamp.

Main chassis ground to rear body connection.

Dedicated fuel tank sender ground to rear body connection.

If your car is a 1953-57 model, plug in one of the 1953-57 courtesy lamp extensions from the 510280 kit here.

12v battery feed to LH underdash courtesy lamp for 1953-57 applications only.


Switched ground to LH underdash courtesy lamp for 1953-57 applications only.

Plug into existing LH door jamb switch (not included with this kit).

Ground to LH door jamb switch.

Switched ground to LH door jamb switch.

Main chassis ground to LH dash frame / kick panel area (dash bird cage assembly).



RESTO MOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

PART #

VCU5362

DESCRIPTION:

1953-62 Chevy Corvette RestoMod Series

92973594 Rev. 0.0 5/31/2022

Bag

G

Circuit Branch 3 - Underdash Connections

Wire #	Wire Color	Printing
Lighting Switch		
2A	Red	12v Bat
8A, B	Gray	Dash Lights
9A	Brown	Park Lights
9B	Brown	Rear Running Lamps
10	Yellow	Dimmer Sw Feed
40	Orange	12v Battery Fused
156A, B	White	Ctsy Ground
Ground Lead		
150B,C,D	Black	Ground

Brake Light Switch

40C,D	Orange	12v Battery Fused
17A	White	Brake Sw
17B	Lt. Blue	Third Brake Light

Circuit Branch 4 - Underdash Connections

Wire #	Wire color	Printing
Wiper Switch Feed		
93	White	Wiper Feed
Ignition Switch		
2E	Red	12v Bat
3A,B	Pink	Ignition Feed
4	Brown	Ignition Sw Accessory
130	Brown/White	

5

5	Purple	Neutral Safety Switch
Parking Brake Warning Lead		
39C,G	Pink	12v Ign Fused

Main Power, Starter, and Ignition Feed Wires

2B	Red	12v Bat
3A	Pink	Ignition Feed
6	Purple	Starter Soleniod

Engine Connector

31A	Dk. Blue	Oil Pressure
35E	Dk. Green	Temp Sender
39E	Tan	Electric Choke
121	White	Coil Tach
130	Brown/White	
400	Yellow	VSS Ground
401	Purple	VSS Signal
402	Purple/White	VSS Power

Instrument Cluster Connections

8A,C,E	Gray	Dash Lights
11B	Lt. Green	Hi Beam Indicator Light
14B	Lt. Bue	Left Turn Ind
15B	Dk. Blue	Right Turn Ind
30	Tan	Gas Gauge
31	Dk. Blue	Oil Pressure
35A	Dk. Green	Temp Sender
39 wires	Pink	12v Ign Fused
121	White	Coil Tach
139	Pink/White	Speedo Power
150 wires	Black	Ground
151	Black	Ground
400	Yellow	VSS Ground
401	Purple	VSS Signal
402	Purple/White	VSS Power

Cigarette Lighter

140	Orange	12v Battery Fused
-----	--------	-------------------

Procedure

Plug this connector onto lighting switch 510284.
Unfused 12v battery feed to the lighting switch for headlamps.
Feed out to dash illumination lamps at cluster.
Feed out to front parking lamps.
Feed out to rear tail lamps.
Feed to headlight dimmer switch for headlights.
Secondary fused 12v battery feed to lighting switch forparking, tail, dash illumination, courtesy, and dome lamps.
Switched ground for courtesy and dome lamps.
Main H/L switch ground. Plug this black connector onto the male blade on the side of the new 510284 lighting switch.
Chassis ground to lighting switch to operate the courtesy and dome lamps.

Plug each these connectors onto either one of the brake light switch blades. **NOTE:** This harness is set up for the '58-'62 style brake switch which utilized 2 male blade terminals. If your car is a '53-'57 model which utilized a male pin type connection, plug extension wires 40X and 17X (as found on page 3 of this instruction set) onto wires 40C,D and 17A,B and then plug those extensions onto your brake switch.
12 volt fused battery feed the stop lamp switch.
12 volt switched feed out to turn signal switch.
12 volt switched feed out to third brake light circuit at rear body connector.

Procedure

This is your 12v feed only. This feed must be used in conjunction with your original wiper motor or as the 12v power for any aftermarket switch/motor assembly. **NOTE:** If you are using a stock wiper motor, a ground wire, 150X (as found on page 3 of this instruction set), has been provided for you to ground your wiper motor assembly.
12v fused feed for wiper switch assembly or motor.

Plug this connector onto the 510621 ignition switch.
Unfused feed into ignition switch from the battery.
Unfused ignition feed out to fuse panel and ignition system.
Unfused accessory feed out to fuse panel.
Altenator regulator exciter feed from the ignition switch to the engine connector. **NOTE:** This 10 OHM resistance wire is doubled with the brown 4 wire at the "ACC" terminal an the ignition switch.
Unfused start feed to the neutral safety switch.

Optional parking brake warning kits 510327 or 510328 will plug into this feed (**optional kits not included with this kit**).
Fused 12 volt ignition feed for optional extra cost parking brake warning kit ('53-'57 kit, 510327; '58-'62 kit, 510328).

Plug the main power connector from the 510915 Front Light and Main Power Kit onto the dash connector, then route the wires out through the firewall. Connect these wires to your Megafuse assemblies, the starter solenoid, and your ignition system (Coil, HEI, MSD, ECU, etc.). See page 10, "Figures C and D" for typical connections. These wires will route to the engine bay with the engine harness wires. For loose piece terminals and connectors, see kit 510894.

Unfused 12v battery feed from your battery source to the fuse panel.
Unfused ignition feed from the ignition switch to your ignition system.
Unfused starter solenoid feed from the neutral safety switch to the "S" terminal on your starter solenoid.


Plug the engine harness extension (as found on page 3 of this instruction set) onto this connection. See **NOTE 1** on this page to the right. See page 10, Figure C for typical connections. See loose piece kit 510894 for any needed terminals and connectors.

Oil pressure signal from engine connector to the cluster connection.
Temperature sender signal from engine connector to the cluster connection.
12v ignition feed for the electric choke from fuse panel to the engine connector.
Tach sender signal wire from engine connector to the cluster connection.
This is the low voltage feed wire for a GM Style "SI" internally regulated alternator from the ignition switch.
VSS ground from engine engine connector to the cluster connection for electric speedometer.
VSS signal from engine engine connector to the cluster connection for electric speedometer.
VSS 12v fused power from cluster connection to engine connector to the cluster connection for electric speedometer.

These connections will plug into the Cluster Connection Kit, 510278. Specific connections are addressed in that kit.

12v feeds out from the lighting switch to the cluster connections for dash illumination lamps.
12v feed to the cluster for high beam indicator lamp.
12v feed to the cluster for left front turn indicator lamp.
12v feed to the cluster for right front turn indicator lamp.
Fuel sender signal from rear body harness connection to the cluster connection.
Oil pressure signal from engine connector to the cluster connection.
Temperature sender signal from engine connector to the cluster connection.
Fused 12v Ignition feeds to cluster connections for any stock or aftermarket electrical gauges.
Tach sender signal wire from engine connector to the cluster connection.
Fused 12v Ignition feed to the cluster connection for electric speedometer.
Gauge cluster ground to cluster connections.
Electric speedometer ground to the cluster connection for electric speedometer.
VSS ground to the cluster connection for electric speedometer.
VSS signal to the cluster connection for electric speedometer.
VSS 12v fused power to the cluster connection for electric speedometer.

Plug this connection onto your original lighter socket assembly. A 1953-57 lighter ground wire (150Z) has also beenprovided and can be found on page 3 of this instruction set. It installs exactly as your original did.
12v battery feed for the cigarette lighter.



NOTE 1: On page 3 you will find the engine harness extension wiring along with several loose wires that can be plugged into the engine harness extension plug. In a stock application, the only engine wire necessary would be the dark green temperature gauge wire. The other feeds in the "engine connector" to the right are for electric tach and gauges, an electric choke, and an alternator ignition feed.


Please see the engine harness extension wiring on page 3 and choose the wires that you need based on your application. Plug any chosen loose piece wires into the main connector of the extension harness being sure to maintain color continuity with the engine connector on the dash harness to the right. Once this has been completed, plug the engine harness extension wiring onto the engine connector to the right, and route those wires, along with the 2B, 3A, and 6 wires, out through your firewall into the engine bay, and onto your engine senders, coil, alternator, etc.

RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

PART #
VCU5362
DESCRIPTION:
1953-62 Chevy Corvette
RestoMod Series
92973594 Rev. 0.0 5/31/2022

TYPICAL BLADE TYPE GAUGE CONNECTIONS




Typical 3 wire Autometer 5291 VSS connection

Note:
This VSS requires a lead wire from the red wire to a 12 volt ignition source. This wire is not included in the kit.



Typical 2 wire VSS connection



Note: Your VSS Signal and Ground wires have been twisted together from the factory and must remain this way to shield out any outside electrical interference that may create an issue with the proper operation of your electric speedometer.

Circuit Branch 4 - Instrument Cluster Wiring
Shown is a typical installation with electric gauges and an electronic speedometer and tachometer. Mechanical speedometers will only require the light leads. The VSS lead wires can be ignored for mechanical speedometers. Always check the manufacturers instructions for specific requirements.

PART #	Bag
VCU5362	G
DESCRIPTION:	
1953-62 Chevy Corvette	
RestoMod Series	
92973594	Rev. 0.0 5/31/2022

RESTO MOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

Main Fuse Panel Installation Instructions

Circuit Branch 5 - Underdash Connections

Wire #	Wire Color	Printing
Back Up and Neutral Safety Switch Connections		
24	Lt. Green	Back Up Lt Sw
39C	Pink	12v Ign Fused
5	Purple	Neutral Safety Sw
6	Purple	Starter Solenoid

Turn Signal Switch Connection

14A, B	Lt. Blue	Left Front Turn
15A, B	Dk. Blue	Right Front Turn
16B	Purple	Turn Switch Feed
17A	White	Brake Sw
18	Yellow	Left Rear Turn
19	Dk. Green	Right Rear Turn
27B	Brown	Turn Sw Hazard

Circuit Branch 6 - Underdash Connections

Wire #	Wire Color	Printing
Heat and A/C Feed		

50	Brown	Heater AC Feed
----	-------	----------------

Radio Connections		
43	Tan	Radio
99B	Yellow	Radio Battery
8D	Gray	Dash Lights

Clock Connections

8B, D	Gray	Dash Lights
99A	Yellow	Radio Battery

Ground		
150F, G	Black	Ground

1958-62 Center Dash Courtesy Connection

40D, E	Orange	12v Battery Fused
156B, D	White	Ctsy Ground

1953-57 RH Courtesy Connection

40E	Orange	12v Battery Fused
156D, E	White	Ctsy Ground

LH Door Jamb Switch		
150C	Black	Ground
156C	White	Ctsy Ground

Electric Speedo Ground Lead		
151	Black	Ground

Procedure

A typical connection for your neutral safety and back up switch can be found on page 10, "Figure E". **NOTE:** If you are running a manual transmission, and are not running neutral safety switch, you must connect the 5 and 6 wires together.
Switched feed from back up lamp switch to rear body connection.
12v ignition feed to back up lamp switch.
12v feed from solenoid post on the ignition switch to neutral safety switch.
12v starter solenoid feed out to engine connections from neutral safety switch.

Plug into steering column turn signal connection. If you are using a stock '53-'62 Corvette steering column in your car, please refer to "Table A - Kit turn signal wires to stock Corvette turn signal switch" on page 8 for proper mating directions. Our connector mates to a 3 7/8 inch long plug used on 1969-1974 GM, IDIDIT, and many other aftermarket steering columns. Starting from 1975 on up, the GM switch changed and began using a 4 1/4 inch connector. That connector is from the same family and uses the same terminals. By using the supplied mating connector and terminals located in the loose piece kit bag of the dash/main harness (510894), it is easy to adapt any steering column to this kit. The function of the wires are as follows:
LH front turn signal feed out to front light and dash cluster connections.
RH front turn signal feed out to front light and dash cluster connections.
Turn signal 12v feed into column from turn flasher.
12v input from brake switch to turn switch for rear brake lights.
LH rear turn signal feed out to rear body connection.
RH rear turn signal feed out to rear body connection.
Hazard switch 12v feed into column from hazard flasher.

Procedure

This wire will plug onto your stock heater switch or can be used as the "on/off" power source for aftermarket A/C.
NOTE: We have also provided you with a blower motor ground wire (150Y) in the event that you are using a stock heater in your car. That wire can be found on page 3 of this instruction set and connects exactly as your original did, from the blower motor case to a chassis ground.
12v switched feed for "on/off" power to your stock heater switch or aftermarket heat and A/C.

12v fused accessory feed for radio "on/off" power.
12v fused battery feed for radio memory.
12v feed out from the lighting switch to the factory radio lamp.

NOTE: We have included a clock lamp extension which can be found on page 3 of this instruction set. Depending on what year your car is, there are 3 different possible configurations that can be used. Please refer to the detail drawing on page three to complete the proper extension for your car. Once completed, plug the extension onto wires 8B, D to complete the lamp circuit for your factory in dash clock.
12v feed out from the lighting switch for the factory clock lamp.
12v fused battery feed for factory clock assembly.


Main chassis ground to RH dash frame / kick panel area (dash bird cage assembly).

If your car is a 1958-62 model, plug in the 1958-62 center courtesy lamp extension with lamp socket from the 510280 kit here.
12v battery feed to RH underdash courtesy lamp for 1958-62 applications only.
Switched ground to RH underdash courtesy lamp for 1958-62 applications only.

If your car is a 1953-57 model, plug in one of the 1953-57 courtesy lamp extensions from the 510280 kit here.
12v battery feed to RH underdash courtesy lamp for 1953-57 applications only.
Switched ground to RH underdash courtesy lamp for 1953-57 applications only.

Plug into existing LH door jamb switch (not included with this kit).
Ground to LH door jamb switch.
Switched ground to LH door jamb switch.

Attach this wire to a good known chassis ground. (Note: Do not attach this wire with the 150F,G wires)
Chassis ground for electric speedometer at instrument cluster connection.



RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

PART #

VCU5362

DESCRIPTION:

1953-62 Chevy Corvette
RestoMod Series


92973594 Rev. 0.0 5/31/2022

Bag


G

NOTE: On this page, you will find a photograph of the stock firewall in a typical 1953-62 Corvette. Your new harness has been designed so that the forward lamp and engine wiring will pass through the original firewall pass through locations. We have NOT provided you with any firewall pass through grommets, as we have left that option to the customer. Please be sure to line the opening in your firewall in some fashion so that you do not chaff your new harness. There is also sufficient length on the new harness for custom routing if you have closed this stock hole up and wish to route the wires out into the engine compartment in a different manner. See pages 9 and 10 for the specific connection and routing instructions of all your forward lamp and engine wiring.

**Stock Firewall
Harness Pass
Thru Grommets**



Front Light Wiring




Engine Wiring

**As Viewed From
Under the Hood**

“Table A”
Kit Turn Signal Switch wires to stock
1953-62 Chevy Corvette turn signal switch.

LL Wire #	LL Wire color	LL Wire Printing	Stock Corvette Wire Color
14A,B	Light Blue	Left Front Turn	Light Blue
15A,B	Dark Blue	Right Front Turn	Dark Blue
16B	Purple	Turn Switch Feed	Yellow
17A,B	White & Blue	Brake Switch	White
18	Yellow	Left Rear Turn	Pink
19	Dark Green	Right Rear Turn	Purple
27B	Brown	Turn Sw - Hazard	Not applicable
28	Black	Horn Relay Ground	Black, Tan, or Dk. Green

NOTE: The stock 1953-62 Corvette turn signal switches did not have a horn ground wire located in them. That wire was a separate wire that was attached to the steering column upper mast jacket bushing and came out through an opening in the steering column. That wire was typically black, tan, or dark green and had an small male blade crimped onto it. If you are using the factory steering column in your car, crimp one of the loose piece terminals M found in the loose piece kit of the 510894 dash harness onto that wire, and plug it into the adapter L when building your turn signal switch adapter to complete the horn ground circuit.



Stock 1953-62 Steering Column Wiring

PART #

VCU5362

DESCRIPTION:


**1953-62 Chevy Corvette
RestoMod Series**

92973594 Rev. 0.0 5/31/2022

Bag

G

Figure "A", Front Light Harness Connections



This kit also utilizes headlight bucket extension harness 510281 that must also be used in conjunction with the dash/main harness to complete the front light circuits.

A close-up photograph of the interior of a red car body. A black braided hose is connected to a metal terminal on the red metal. Several white wires are also visible, some connected to the same terminal area. The red paint is glossy and reflects light.


RH passenger side inner panel



LH driver side inner panel

RESTO-MOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.
www.lectriclimited.com 708-563-0400

SEE PAGE 3 FOR MAIN
POWER CONNECTIONS



NOTE: The terminals and connectors listed on this page and denoted with **UPPER CASE LETTERS** to help you complete the various connections to your ignition, temp and oil senders, electric choke, starter solenoid, alternator regulator, etc. are included and can be found in the dash/main loose piece parts kit, P/N 510894. No terminals have been provided for the neutral safety or back up connections.

The identifications, colors, and functions for all of the wires listed in Figures "C, D, and E" on this page can be found on branch 4, page 5, and branch 5, page 7 of this main instruction set (92973594). We suggest and recommend using pages 5 and 10 to complete the installation of the engine, main power feed, NS-S/back up, and alternator connections.

A note about alternators: Our kits are all engineered to be used in conjunction with a high output, later model internally regulated, or one wire alternator. We do not suggest or support the use of a stock low amperage generator or alternator as they do not supply sufficient current to recharge the battery in a highly modified vehicle such as this kit was designed for. We suggest GM "SI", or 1 wire type alternators as good choices to use. Adapters to complete the other style alternator connections may be purchased separately if needed. Contact Lectric Limited for your needs.

Figure "D" Alternator Wiring


2F Red

This is the "SI" alternator regulator plug. Install the ring terminal onto the alternator battery stud and route the connector to the regulator position on the alternator. The brown 25 wire from the engine harness will install into the empty cavity of this connector as shown on page 10 Figure D, and the finished assembly will then plug into the alternator to complete your alternator connection.

NOTE: If you are using a 1 wire alternator, the 2F and 25 wires will not be used.



Figure "E"
Shown is a typical NSS and Back Up Switch.




RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.
www.lectriclimited.com 708-563-0400

PART #
VCU5362
DESCRIPTION:
**1953-62 Chevy Corvette
RestoMod Series**
92973594 Rev. 0.0 5/31/2022

Bag
G


Fuse Box lid



Fuse label on inside of Fuse Box lid

Fuel Pump 20A - IGN	16	8	Pwr. Window 30A - IGN
Elec. Choke 15A - IGN	15	7	Hazard 15A - BAT
Gauges, B/U 10A - IGN	14	6	Stop/Courtesy 15A - BAT
Turn 15A - IGN	13	5	Power Locks 15A - BAT
Engine Fan 30A - ACC	12	4	Park Lights 15A - BAT
Radio 10A - ACC	11	3	Power Seat 30A - BAT
Heat/AC 30A - ACC	10	2	Clock/Radio 15A - BAT
Wiper 20A - ACC	9	1	Batt - Spare 30A - BAT

Fuse Values and Locations



Fuse/Circuit table

Fuse #	Fuse Block Cover Label	Fuse Rating	Description
1	Bat-Spare	30A	Battery feed spare
2	Clock - Bat	15A	Battery feed for a Clock and a Radio.
3	Power Seats	30A	Battery feed for optional Power Seats.
4	Park Lights	15A	Battery feed for Park Lights.
5	Power Locks	15A	Battery feed to Power Locks.
6	Stop / Courtesy	15A	Battery feed for Brake Lights and Courtesy Lights.
7	Hazard	15A	Battery feed for optional Hazard Lights and optional battery feed.
8	Power Window	30A	Ignition feed for optional Power Windows.
9	Wiper	20A	12V Accessory feed for Wiper/Washer system.
10	Heat / AC	30A	12V Accessory feed for Heater/AC System.
11	Radio	10A	12V Accessory "on-off" feed to Radio.
12	Engine Fan	30A	12V Accessory for an optional Electric Fan System, Relay key-on trigger
13	Turn	15A	Ignition feed for the Turn Signals.
14	Gauges, B/U	10A	Ignition feed for Dash Gauges/Warning Lights and Back Up Lights
15	Electric Choke	15A	Ignition feed for an Electric Choke, ECM Ignition Feed
16	Fuel Pump	20A	Ignition feed for an Electric Fuel Pump

RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

PART #

VCU5362

DESCRIPTION:

1953-62 Chevy Corvette RestoMod Series

92973594 Rev. 0.0 5/31/2022

Bag

G

**THIS PAGE INTENTIONALLY
LEFT BLANK**

RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

PART #	VCU5362	Bag
DESCRIPTION:	1953-62 Chevy Corvette RestoMod Series	G
92973594	Rev. 0.0	5/31/2022

INSTRUCTIONS FOR INDIVIDUALLY BAGGED ITEMS WITHIN THIS KIT


RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

1953 - 1962 Corvette Fuse Panel Mounting Template and Instructions


Stock F/L
Harness Hole

Custom F/L
Harness Hole



NEW application

Stock F/L
Harness Hole



Original application

As Viewed From Under the Dash

NOTE:

1. The installation and placement of the new fusebox is not extremely critical for this application. On this page, you will find a photograph of the completed fusebox and dash harness as they were installed in our 62 Pro-Touring Corvette along with a before photo of the stock configuration. Take note of the stock front light harness hole location to the left of the stock fusebox. Our 62 Pro-Touring car had the front light hole relocated up and over the top of the new fusebox so that it routed thru some PVC tubing up underneath the LF fender area instead of along the inside of the LH inner fender. The harness is long enough that you just need to mount the fusebox as the photo depicts. As long as the fusebox assembly is installed in the general area as shown, the harness will install fine.

2. Be sure to check for clearances of any accessories that you might be adding. The stock clutch and brake pedal assembly pose no concerns at all when mounted in this location. There are 2 mounting holes (1 each) on the upper and lower tabs of the fusebox case. Using the fusebox as a template, drill 2 new 11/64" holes in your firewall. 2 new attaching screws and locking nuts have been provided for you to affix the fusebox to the firewall. They can be found in the 510894 loose piece dash kit.

3. Once the fusebox has been attached to the firewall of the car, the harness routes up and over top of the pedal carriage assembly and steering column in behind the speedometer assembly, then along the bottom of the dash frame and over to the RH door jamb area. Please take time to keep it away from any moving items such as the wiper motor linkage.

RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

92969889

92969889 instructions Rev 2.0 7/7/2022

*** These are special instructions for connecting your wiring system to the stock instrument clusters. ***

Note: If you are using aftermarket gauges, follow the instructions included in the 92968220 Gauge Connection Kit along with the specific gauge manufacturers instructions for connection of their gauges.

If you are using the stock gauges, refer to the diagrams on the following pages for your application. Use the enclosed parts and information below for wire termination, gauge, and lamp connections. Connectors A,B,C, and D will plug into your dash harness as noted on the Dash Harness instruction set (510277, bag G). Connection D will only be used in the event that you are using an electric speedometer.

CONNECTOR A (sheet 2)

DK BLUE	Right Turn Indicator	Install components as shown on sheet 2, and plug into the right turn hole in cluster.
LT BLUE	Left Turn Indicator	Install components as shown on sheet 2, and plug into the left turn hole in cluster.
LT GREEN	Hi Beam Indicator Lamp	Install components as shown on sheet 2, and plug into the high beam hole in cluster.
GRAY	Instrument Lamps	Install components as shown on sheet 2, and plug into the instrument lamp holes in the speedometer cluster and tach housing.
BLACK	Ground	Connect to the back of the speedometer cluster housing ('58-'62) using ring terminal C (smaller hole), or under the LH mounting bolt of the speedometer cluster ('53-'57) using ring terminal D (larger hole) as shown on sheet 2.
PINK	12v ignition (loose wire)	If your car is equipped with an electric tach requiring a 12v ignition feed, plug this loose wire into Connector A maintaining color continuity with the mating connector on your dash harness, install components as shown on sheet 2, and attach to the tachometer per the manufacturer's instructions..
WHITE	Tach (loose wire)	If your car is equipped with an electric tach, plug this loose wire into Connector A maintaining color continuity with the mating connector on your dash harness, install components as shown on sheet 2, and attach to the tachometer per the manufacturer's instructions.

CONNECTOR B (sheet 3)


DK GREEN	Temp Gauge	Install components as shown on sheet 3, and attach to the temperature gauge sender post.
TAN	Fuel Gauge	Install components as shown on sheet 3, and attach to the fuel gauge sender post.
PINK	12v ignition	Install components as shown on sheet 3, and attach to the fuel and temp gauge 12v ignition feed posts.
GRAY	Instrument Lamps	Install components as shown on sheet 3, and plug into the instrument lamp hole in the fuel and temp gauge pod cluster.

CONNECTOR C (sheet 3)

GRAY	Instrument Lamps	NOTE: The oil pressure gauge was a mechanical unit on a stock Corvette and the stock original ammeter is not supported in this aftermarket upgraded kit, so if you are using the stock gauges, you will only use the gray lamp wire for this cluster pod assembly. Install components as shown on sheet 3, and plug into the instrument lamp hole in the ammeter and oil gauge pod cluster.
DK BLUE	Oil Gauge (loose wire)	If your car is equipped with an aftermarket electric oil pressure gauge, plug this loose wire into Connector C maintaining color continuity with the mating connector on your dash harness, install components as shown on sheet 3, and attach to the oil pressure gauge per the manufacturer's instructions.
PINK	12v ignition (loose wire)	If your car is equipped with an aftermarket electric oil pressure gauge or voltmeter requiring a 12v ignition feed, plug this loose wire into Connector C maintaining color continuity with the mating connector on your dash harness, install components as shown on sheet 3, and attach to the oil pressure gauge or voltmeter per the manufacturer's instructions.
BLACK	Ground (loose wire)	If your car is equipped with an aftermarket voltmeter, this is the ground for that voltmeter. Attach the factory ring terminal end of this wire to the grounding location on the bottom of the dash on a "53-"57 car, or to the lighter and clock ground location on a '58-'62 car, and attach the other end to the voltmeter (-) terminal as shown on sheet 3 and per the manufacturer's instructions.

CONNECTOR D (sheet 4)

This connector is used when using an aftermarket electronic speedometer only. Follow the manufacturer's instructions when installing these wires. If you are using the stock speedometer, then discard this connector. See page 4 for wire descriptions and typical connctions.




RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.


www.lectriclimited.com 708-563-0400



RestoMod Series




RestoMod Series



1953-1962 CORVETTE FUEL AND TEMP GAUGE POD CONNECTIONS

sheet 3

Optional upgraded electric oil pressure and voltmeter connections depicted below. If your car uses the stock mechanical oil pressure gauge, these connections WILL NOT be used. This kit DOES NOT support the use of an ammeter.



1953-1962 CORVETTE AMP AND OIL GAUGE POD CONNECTIONS

92969876 instruction rev 1.0 12/28/2016




TYPICAL ELECTRIC SPEEDO CONNECTIONS


Below are some general instructions for hooking up an electric speedometer. This connector and these instructions will ONLY be used in the event that you are utilizing an aftermarket electric speedometer. If your car does NOT have an electric speedometer, this connection will NOT be used and should not be plugged onto your dash harness. It is best to consult the speedometer manufacturer's instructions if you have any questions.

<u>Yellow</u>	VSS Ground	Connect to VSS "-" on speedometer.
<u>Purple</u>	VSS Pulse	Connect to VSS input on speedometer.
<u>Purple/White</u>	VSS Power	Connect to 12V power on speedometer.
<u>Black/White</u>	Speedo Ground	Connect to ground on speedometer.
<u>Pink/White</u>	Speedo Power	Connect to 12v power on speedometer. <u>NOTE:</u> This wire will double onto the same stud as the purple/white VSS power wire from above.

sheet 1








www.lectriclimited.com 708-563-0400



1953-1960 Corvette (See sheet 1)

Connect the main connector to the mating connector on the dash harness 510277 bag G. Route this harness down the driver's door sill & into the trunk.
LIGHT BLUE Third brake light



TAN

BLACK/WHITE

BROWN

YELLOW

DK GREEN

ORANGE

BLACK

Fuel Tank Sender

(No Printing)

Running lamps

LH Stop / Tail

RH Stop / Tail

12V Battery Feed

Ground

If you are using a third brake light, plug this wire into the main connector maintaining color continuity with the dash/main harness, P/N 510277, then connect the loose end of the wire to your third brake lamp assembly.

Route this wire to the rear of the car close to the exit hole in the trunk floor, then down to the fuel tank sender, install terminal H and attach to the sending unit to complete the fuel tank sender connection.

This is your dedicated fuel tank sender ground lead. Route this wire to the rear of the car (along the side of the tan fuel tank sender wire from above) close to the exit hole in the trunk floor, then down to the fuel tank sender area, install terminal H and attach to the frame of the sending unit to complete the fuel tank sender ground connection.

Note: Two new license lamp leads C have been provided for you. If you are doing a '53-'55 car, you will need to re-use your old lamp sockets as they are not available. If you are doing a 1956-60 car, assemble the extension leads using socket, insert, spring and rivet, D, E, F, and G as shown on sheet 1. These finished extensions will plug onto connectors B as shown on sheet 1 to complete your two license lamp connections. Also, new Stop/Tail lamp pigtailed R and S (yellow and brown for LH driver's side, and green and brown for RH passenger's side) along with ground wires Q have been provided. Install terminal P on each wire and plug them into connector N maintaining color continuity as shown on sheet 1. These pigtailed will plug onto connectors M to complete your rear lighting in a step below.

Route this wire to the LH tail lamp area, cut to length, double this wire with the cut off portion, install terminal K and plug into connector M in the location shown on sheet 1 maintaining color continuity with the LH tail lamp pigtail from above. Route the loose end of this brown wire to the LH license lamp area, cut to length, double this wire with the cut off portion, install terminal A and plug into connector B as shown on sheet 1. Route the loose end of this brown wire to the RH license lamp area, cut to length, double this wire with the cut off portion, install terminal A and plug into connector B as shown on page 1. Route the loose end of this brown wire to the RH tail lamp area, cut to length, install terminal L and plug into connector M in the location shown on sheet 1 maintaining color continuity with the RH tail lamp pigtail from above. Do not plug your completed tail lamp pigtailed from above onto this connection yet.

Route this wire to the LH tail lamp area, cut to length, install terminal L and plug into the empty cavity of connector M as shown on sheet 1 maintaining color continuity with the LH tail lamp pigtail from above. Do not plug your completed LH tail lamp pigtail from above onto this connection yet. Plug LH pigtail B (yellow, brown and black wires) from above onto this connection to complete the LH stop, turn, and tail circuits.

Route this wire to the RH tail lamp area, cut to length, install terminal L and plug into the empty cavity of connector M as shown on sheet 1 maintaining color continuity with the RH tail lamp pigtail from above. Do not plug your completed RH tail lamp pigtail from above onto this connection yet. Plug RH pigtail B (dk green, brown and black wires) from above onto this connection to complete the RH stop, turn, and tail circuits.


If your car has a trunk lamp or you are using LED tail lamps that require a 12v fused battery feed, plug this wire into the main connector maintaining color continuity with the dash/main harness, P/N 510277, then connect the loose end of the wire to the trunk lamp or 12v battery feed for the LED tail lamps.

Note: Four new tail lamp ground wires Q have been provided for you. Only two will be used in this application as outlined above.

Route this wire to the LH tail lamp area, cut to length, double this wire with the cut off portion, install terminal K and plug into connector M in the location shown on sheet 1 maintaining color continuity with the LH tail lamp pigtail from above. Route the loose end of this black wire to the LH license lamp area, cut to length, double this wire with the cut off portion, and install terminal J as shown on sheet 1. **If your car is a '53-'55 car**, route the loose end of this black wire to the RH license lamp area, cut to length, double this wire with the cut off portion, and install terminal J as shown on sheet 1. **Continuing with a '53-'55 car**, route the loose end of this black wire to the RH tail lamp area, cut to length, install terminal L and plug into connector M in the location shown on sheet 1 maintaining color continuity with the RH tail lamp pigtail from above. **If your car is a '56-'60 car**, route the loose end of this black wire to the RH tail lamp area, cut to length, install terminal L and plug into connector M in the location shown on sheet 1 maintaining color continuity with the RH tail lamp pigtail from above. You may now plug your completed tail lamp pigtailed from above onto these two tail lamp connections. Your rear body connections are now completed.

RestoMod Series

NOTE: Back up lamps on an early Corvette were never offered. If your car has been customized to add them, you will need to purchase the optional Back Up Lamp kit, P/N VCU6162BU, to make those connections. If your car has been customized to add a third stop/tail lamp assembly the rear of your car, you will need to purchase the optional 3rd Stop/Tail Lamp kit, P/N VCU6162TL, to make those connections.



1961 - 1962 Corvette without Back Up Lamps. (For a car with Back Up Lamps, see kit number VCU6162BU. Also, for a car with 3 Stop/Tail Lamps, see kit number VCU6162TL)

RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400



1961 - 1962 Corvette without Back Up Lamps (See sheet 3)


A			Connect the main connector to the mating connector on the dash harness 510277 bag G. Route this harness down the driver's door sill & into the trunk.
B		LIGHT BLUE	Third brake light If you are using a third brake light, plug this wire into the main connector maintaining color continuity with the dash/main harness, P/N 510277, then connect the loose end of the wire to your third brake lamp assembly.
C		TAN	Fuel Tank Sender Route this wire to the rear of the car close to the exit hole in the trunk floor, then down to the fuel tank sender, install terminal H and attach to the sending unit to complete the fuel tank sender connection.
D		BLACK/WHITE	(No Printing) This is your dedicated fuel tank sender ground lead. Route this wire to the rear of the car (along the side of the tan fuel tank sender wire from above) close to the exit hole in the trunk floor, then down to the fuel tank sender area, install terminal H and attach to the frame of the sending unit to complete the fuel tank sender ground connection.
E			Note: Two new license lamp leads C have been provided for you. For the 1961-62 application, you will only be using one of these pigtails. On a 1961-62 car, assemble the extension lead using socket, insert, spring and rivet, D, E, F, and G as shown on sheet 3. This finished pigtail extension will plug onto connector B as shown on sheet 3 to complete your license lamp connection. Also, four new Stop/Tail lamp pigtails R and S (2 yellow and brown for LH driver's side, and 2 dk green and brown for RH passenger's side) along with four ground wires Q have been provided. Double the LH yellow wires together and then LH brown wires together, install terminal A on each connection and plug the yellow and the brown doubled wires into connector N maintaining color continuity as shown on sheet 3. Repeat this process for the RH dk green and brown wires. Double two of the ground wires Q together, install terminal A on each connection and plug the black doubled wires into connector N maintaining color continuity as shown on sheet 3. These pigtails will plug onto connectors M to complete your rear lighting in a step below.
F			
G			
H			
J		BROWN	Running lamps Route this wire to the LH tail lamp area, cut to length, double this wire with the cut off portion, install terminal K and plug into connector M in the location shown on sheet 3 maintaining color continuity with the LH tail lamp pigtail from above. Route the loose end of this brown wire to the license lamp area, cut to length, double this wire with the cut off portion, install terminal A and plug into connector B as shown on sheet 3. Route the loose end of this brown wire to the RH tail lamp area, cut to length, install terminal L and plug into connector M in the location shown on sheet 3 maintaining color continuity with the RH tail lamp pigtail from above. Do not plug your completed tail lamp pigtails from above onto this connection yet.
K			
L			
M		YELLOW	LH Stop / Tail Route this wire to the LH tail lamp area, cut to length, install terminal L and plug into the empty cavity of connector M as shown on sheet 3 maintaining color continuity with the LH tail lamp pigtail from above. Do not plug your completed LH tail lamp pigtail from above onto this connection yet.
N		DK GREEN	RH Stop / Tail Route this wire to the RH tail lamp area, cut to length, install terminal L and plug into the empty cavity of connector M as shown on sheet 3 maintaining color continuity with the RH tail lamp pigtail from above. Do not plug your completed RH tail lamp pigtail from above onto this connection yet.
P		ORANGE	12V Battery Feed If your car has a trunk lamp or you are using LED tail lamps that require a 12v fused battery feed, plug this wire into the main connector maintaining color continuity with the dash/main harness, P/N 510277, then connect the loose end of the wire to the trunk lamp or 12v battery feed for the LED tail lamps.
Q		BLACK	Note: Four new tail lamp ground wires Q have been provided for you. Installation info these wires is outlined in the Note above. Route this wire to the LH tail lamp area, cut to length, double this wire with the cut off portion, install terminal K and plug into connector M in the location shown on sheet 3 maintaining color continuity with the LH tail lamp pigtail from above. Route the loose end of this black wire to the license lamp area, cut to length, double this wire with the cut off portion, and install terminal J as shown on sheet 3. Route the loose end of this black wire to the RH tail lamp area, cut to length, install terminal L and plug into connector M in the location shown on sheet 3 maintaining color continuity with the RH tail lamp pigtail from above. You may now plug the completed LH pigtail R (yellow, brown, and black wires) and the completed RH pigtail S (dk green, brown, and black wires) from above onto these 2 new tail lamp connections to complete the LH and RH stop, turn, and tail circuits. Your rear body connections are now completed.
R			
S			

A

(144.0" 6 Gauge charge wire)

(1)


B



(2)

(Megafuse body, cover and two M8 x 1.25 nuts / lock washers)


C



(2)

(175 amp Megafuse)

D



(1)

(Megafuse jumper)

E



(1)

(Alternator boot)

F



(1)

(cut into six 1.0" pieces)

MEGAFUSE

1. On this page, you will find the wire, fuse bodies, fuses, boot, ring terminals, and shrink tubing (items A through K) that are necessary to connect your alternator and main power feed for your new wiring kit. Please be sure that all of the necessary components are present before starting this portion of your installation. If anything is missing, stop what you are doing and contact us at the number listed below right away.

2. On page 2, you will find directions for building the 2 Megafuse assemblies (items B,C and D) into one unit.

3. On page 3, you will find an overall concept of how to connect the Megafuse assemblies to your starter solenoid, alternator and main power feed of your new wiring system.

4. On page 4, you will find tips on building your charging circuit wires and assembling them and the main panel power feed wire to the Megafuse assemblies.

G



(2)

(6Ga. starter ring terminal)

H



(3)

(6Ga. megafuse terminal)

J



(2)

(6Ga. alternator terminal)

K



(2)

(10Ga. megafuse terminal)

RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

LOT # 898325

PN 510813

PART #


510813

Z

DESCRIPTION:

Alternator and Main Power
Connection Kit
Various Applications


92972934 instruction sheet rev 0.0 3/26/2020




Assembling the (2) Megafuse assemblies

NOTE: Find a suitable place, as close to the battery power source as possible, under the hood of your vehicle to mount the completed Megafuse assemblies. Keep in mind that you have 12 feet of 6Ga. charging wire, and that the main power feed coming from your panel or bulkhead connection must also be able to reach the assembly.

1. Take the two Megafuse bodies and covers (items B) and snap them together. Remove the 4 nuts and lock washers from the studs on the fuse body assemblies.
2. Install the Megafuse jumper (item D above) over two of the studs on the Megafuse bodies. It is very important that the jumper **MUST BE** assembled on the side that is going to connect to your main power connection (starter solenoid or battery feed).
3. Notch top cover to clear jumper D as shown at right.
4. Snap one 175amp fuse (items C) onto the studs of each of the two Megafuse bodies (items B), over the jumper, then loosely re-attach the 4 nuts and lock washers back onto the assembled Megafuses. The fuse assemblies are ready to install into your vehicle.



Assembled Megafuses



Notched Cover

PART #


510813

Z

DESCRIPTION:

Alternator and Main Power
Connection Kit
Various Applications

92972934 instruction sheet rev 0.0 3/26/2020



Building the 6Ga. charge wires and connecting them and the main panel power feed wire to the Megafuse assemblies:

NOTE: Make sure that your battery is disconnected! You will need to install the preassembled Megafuses from page 2 in your vehicle to start this part of the installation.

1. Pre-cut item F shrink tubing into (6) 1.00" - 1.25" pieces.
2. Take the 12-foot piece of 6Ga. red wire from this kit and route it from your starter (or other battery feed) over to the area where you have mounted your Megafuse and cut it to length. Strip the insulation on each end back 1/2". Install 2 pieces of shrink tubing F onto the wire. At the starter end, crimp and solder (1) of terminal G onto the wire. At the Megafuse end, crimp and solder (1) of terminal H onto the wire. Slide the shrink tubing over the terminals and heat it up to shrink it down.
3. Take the remaining portion of the 12-foot piece of 6Ga. red wire from this kit and route it from your alternator over to the area where you have mounted your Megafuse and cut it to length. Strip the insulation on each end back 1/2". Install 1 piece of shrink tubing F onto the wire. At the alternator end, slip on boot E as shown on page 3, then crimp and solder (1) of terminal J onto the wire. At the Megafuse end, crimp and solder (1) of terminal H onto the wire. Slide the shrink tubing over terminal H and heat it up to shrink it down.
4. Take the 10Ga. red main power feed wire from your engine or panel sub-kit and route it over to the area where you have mounted your Megafuse and cut it to length. Strip the insulation back 3/8". Install 1 piece of shrink tubing F onto the wire, then crimp and solder (1) of terminal K onto the wire.
5. Remove the 4 loosely tightened nuts and lock washers from the assembled Megafuses, then using the drawing on page 3 as a guide, install your pre-assembled wires from steps 2-4 above. Re-install the 4 nuts and lock washers onto the assembled Megafuses and tighten them down. This part of your installation is now complete.


510813

Z


DESCRIPTION:

Alternator and Main Power
Connection Kit
Various Applications

92972934 instruction sheet rev 0.0 3/26/2020



92969884



NOTE: Your new '58-'62 underdash courtesy lamp extension uses a # 090 bulb (not included with this kit). It may be purchased separately.



NOTE: There were 2 different courtesy lamp configurations used from 1953 thru 1962. We have included both styles in this kit. Your new main/dash harness (510277, bag G) will service either application. There are three 2-way connections on the dash harness. One at either end that will be used in the 1953 - 57 cars, and one in the middle that will be used in the 1958 - 62 cars.

1. The '53 thru '57 cars used 2 lamp assemblies (one each on the LH and RH sides up under the dash). Each had a 2-wire lead coming off of it that included a fixed lamp socket assembly. The original courtesy lamp harnesses plugged into these fixed lamp assemblies. If your car is a '53 - '57 model, you will take the two '53 - '57 versions as shown above, and plug the main connectors onto the dash harness at either of the two end locations where noted on the dash/main instruction sheet.
2. The '58 thru '62 cars used a single lamp which did have a lamp socket that was a part of the courtesy lamp harness which snapped into a bracket in the center of the dash. If your car is a '58 - 62 model, you will take the single '58 - '62 version with the lamp socket on it as shown above, and plug the main connector onto the dash harness in the center location where noted on the dash/main instruction sheet.

RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400







NOTE: On all 1953 thru 1957 Corvettes, it may be necessary to open up the hole slightly in your dashboard for the new, larger diameter headlight switch retaining nut. The Corvette dash/main harness assembly has a dedicated ground wire connection, so the courtesy lamps will work with, or without, the switch mounted into the dashboard. The 1953 thru 1957 Corvette models used a "D" shaped knob/shaft assembly and a smaller diameter retaining nut, so you will need to use the retaining nut and knob/shaft assembly from this kit as your originals **WILL NOT** work with this newer, updated style switch. If you own a 1957 Corvette, your car is unique in that it used the older style switch with the "D" shaped shaft, but had the newer 1957 style knob. You can purchase a new reproduction 1957 Chevy Passenger car knob/shaft assembly from any Tri-Five supplier that will work with this newer style switch assembly. On all 1958 thru 1962 Corvette models, you will need to use your original retaining nut and knob/shaft assembly (not included with this kit) so that the switch installs properly and so that the knob matches the rest of the knobs in your car.

1. Install the new knob and shaft assembly (or your original knob and shaft assembly if you have a 58-62 Corvette) into the new headlight switch to be sure that all of the internal gates line up inside of the switch. You'll want to be listening for the shaft to "click" into position which will lock the knob and shaft assembly into the switch. Once it locks into place, pull the knob out to the "ON" position, push in on the spring loaded button that is protruding from the metal chassis of the new switch, and you will be able to remove the knob/shaft assembly from the switch.
2. Next, we suggest installing the switch into your dashboard assembly and checking it for the proper fitment. Next, remove the switch from your dashboard until it is ready to be installed.
3. Once you have the dash/main harness installed into the car, plug the new switch into the dash/main harness plug (This is more easily done with the switch not installed into the dashboard assembly), route the harness (with the switch plugged onto to main/dash plug) over to the proper location for the headlight switch, and install the new switch and lead assembly into your dashboard using the new nut or your original nut (depending on what year and model you are working on as discussed in the **NOTE** above).
4. Once installed into the dashboard of your car, you can reinstall the new knob/shaft assembly or your original knob/shaft assembly (depending on what year and model you are working on as discussed in the **NOTE** above). This will complete the new headlight switch installation portion of your kit.

RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.


www.lectriclimited.com 708-563-0400





NOTE: Looking into the face of the connector.
Wires are plugging in from behind.


NOTE: New terminals are provided if needed.



INSTALLATION

NOTE: The instruction sheet packaged with this switch shows a copper lamp holder bracket. That bracket is not used in this application and it's installation can be ignored.

1. Due to the nature of the chrome plating on threaded collar A, we recommend threading the nut on and off of the switch by hand a few times to clean up the threads before installing the switch into your dash.
2. Plug in connector D from the dash wiring harness (bag G).
3. Install the back-up nut C onto the switch. The depth of this nut will have to be determined when mounting the switch.
4. Insert the switch into the hole in the dash panel.
5. Install your original dash bezel plate.
6. Slide on collar B.
7. Screw on threaded collar A
8. Insert your existing lock cylinder into the new switch. This allows you to utilize your original keys



LOT#891262



PART# 510621




RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

IGNITION SWITCH
1953-1962 Corvette

510621

92972602 instruction rev 0.0 10/8/2019



Connect the Dimmer Switch wires as shown above.

1. The top center terminal of the Dimmer Switch is connected to the Headlight switch.
2. The terminal on the right side is connected to your headlight high beam terminal.
3. The terminal on the left side is connected to your headlight low beam terminal.
4. Use the enclosed hardware to attach the new dimmer switch to the top of the floor of your car. This switch does NOT mount under the floor as the original did.

RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

PART #

510285

DESCRIPTION:

DIMMER SWITCH

92969895 instruction sheet Rev 1.0 12/29/2016

1953-1962 Corvette Headlamp Bucket Extension Harness

In this kit, you will find all the components necessary to build the headlight bucket extensions for your car. There were two types of systems, one for dual headlamps ('53-'57), and one for quad headlamps ('58-'62).

The kit consists of the following:

1. Two high beam connectors for a quad H/L system (A).
2. Two low beam connectors for both dual and quad systems (B).
3. Six double 59 Series headlight terminals, which are wider (C).
4. Eight single 59 Series headlight terminals, which are narrower (D).
5. Two 3 way male connectors to plug onto the bare male blades on the three wires (E).
6. Two grommet and loom assemblies (F).
7. Two each lt. green high beam, black ground wires cut at 48" long.
8. Two tan low beam wires cut at 40" long.

Directions:

1. Insert one of each of the three wires (tan, lt. green, and black) into the grommet and loom assembly F at the end opposite the grommet and thread the wire through the assembly and out the end with the grommet attached and even up the connectors at the right end.
2. If your car is a '53-'57 model with dual headlamps, cut the extra eight inches from the lt. green and black wires so that they are all an even length, crimp terminals D onto each wire, and plug into connector B as shown on page 2 of this instruction set.
3. If your car is a '58-'62 model with quad headlamps, cut the extra eight inches from the lt. green and black wires so that they are all an even length. Crimp terminal D onto the tan wire and plug into connector B as shown on page 2 of this instruction set. Double the lt. green wire with cutoff portion of the lt. green wire, crimp terminal C onto those 2 wires and plug into connector B as shown on page 2 of this instruction set. Crimp terminal D onto the loose end of the lt. green wire and plug into connector A as shown on page 2 of this instruction set. Double the black wire with cutoff portion of the black wire, crimp terminal C onto those 2 wires and plug into connector B as shown on page 2 of this instruction set. Crimp terminal D onto the loose end of the black wire and plug into connector A as shown on page 2 of this instruction set.
4. Repeat this process to build your second headlamp extension.
5. Route the loose ends of the two extensions (tan, lt. green, and black wires with the male terminals on them) through the LH and RH inner fender panels of your car and out into the engine bay, then plug the wires into connector E as shown on page 2. These extensions will plug into the dash/main harness (510277, bag G) to complete the headlamp circuits on your car.

page 1

RESTO MOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.



www.lectriclimited.com 708-563-0400



1953 - 1957 (dual headlight system)



1958 - 1962 (quad headlight system)



RESTOMOD SERIES
CORVETTE WIRING SYSTEMS: DESIGNED FOR TODAY. WIRE IT YOUR WAY.

www.lectriclimited.com 708-563-0400

